

## TECHNICAL SPECIFICATIONS

### Building

#### Space

Colocation Space	57,545 ft <sup>2</sup> (5,346 m <sup>2</sup> )
Building Type	1-story, tilt-up concrete slab on grade
Parking	Adjacent to building (no charge)

#### Floor

Floor Type	Slab
Floor Load Capacity	200 psf (9.58 kN/m <sup>2</sup> )

<b>Seismic Design Category</b>	1
--------------------------------	---

<b>Fire Suppression</b>	Double-interlocked, pre-action (dry pipe)
-------------------------	---

### Facilities

#### Power and Cooling

Power and Cooling Density	3.0 - 5.0 kVA per cabinet
UPS Configuration	Block redundant
UPS Redundancy	N+1
Standby Power Configuration	7 x 2,500 kW diesel generators
Standby Power Redundancy	N+1
Cooling Configuration	Split-system, direct expansion, air-cooled, DX CRAC units
Cooling Redundancy	N+1

#### Security

Physical	Man trap entry
Human	24x7 security officers
Electronic	Biometric Readers, Fiber Vault, CCTV and Recorders, Motion Detection

### Amenities

- Break Room
- Loaner Tools
- Showers
- Crash Carts
- Work Kiosks
- Wifi
- Conference Room

### Products and Services

#### Colocation

- Private Cage
- Secure Cabinet
- AC Power Circuits
- DC Power Circuits
- Antenna

#### Interconnection

- Cloud Exchange™
- Internet Exchange
- Cross Connects
- Equinix Management Access
- Campus Cross Connect

#### Services

- Smart Hands™
- Migration Planning
- Equipment Sourcing
- Installation
- Professional Services

#### Packaged Solutions

- Performance Hub™
- Data Hub™

### Reliability

Our IBX data centers boast an industry-leading, high average uptime track record of >99.9999% globally.

### Certification and Sustainability

#### Certifications

- SSAE 16/ISAE 3402 SOC 1 Type II
- SOC 2 Type II
- ISO 27001

#### Green By Design

- Granular temperature controls
- Reflective roof
- LEDs and optimized lighting controls
- Renewable energy - wind